

FP20402N-2-1

Preselector, 150-174 MHz, 1 MHz BW, High Performance, N Female

- Extremely high selectivity, high performance design
- Very compact, low profile VHF preselector for 150-174 MHz
- Easy to tune with very high temperature stability
- Mounted on 19" rack mountable plates

The FP20402N preselectors covers the 130-150 MHz band and 150-174 MHz band. Each preselector is offered with one of three band widths - 0.5 MHz, 1.0 MHz and 2MHz. It weighs 9 pounds / 4.1 Kg with height of 3.5 in / 89 mm, width of 19 in / 483 mm (19" rack mountable), and depth of 17 in / 432 mm. The FP20402N is easy to tune, offers very high temperature stability, provides extremely high selectivity, and low insertion loss, typically less than 1.6 dB operating at Fo.



Application Notes

- Attenuation of 55dB @ fo minus 5 Mhz and 65dB @ fo plus 5 MHz

www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Product Specification Sheet
EPR 018048-2

FP20402N-2-1

Issue: 1


Dated: 22-12-10
Dated: 12-06-06

Electrical Specifications

Frequency Range	MHz	150 to 174
Insertion loss (max) Tx to Ant	dB	1.6
Input VSWR (max)		1.5:1
Number of Cavities		4
Input Connectors		N (female)
Output Connectors		N (female)
Approx Bandwidth @ 50 dB	MHz	7.5
Bandwidth at specified insertion loss	MHz	1

Mechanical Specifications

Length/ Height	in (mm)	3.5 (89)
Width	in (mm)	19 (483)
Depth	in (mm)	17 (432)
Weight	lbs (kg)	9 (4.09)
Mounting configurations		19 inch rack



Environmental Specifications

Temperature range	°F (°C)	-22 to +140 (-30 to +60)
-------------------	---------	--------------------------